



HITCH YOUR TRACTOR TO HIGH PERFORMANCE

REGULAR WITH ROTARY DRUM	1 auger only		1 or 2 augers		
	N98-340H	N102-340H	N98-342H N98-342HTR	N102-342H N102-342HTR	N112-342H N112-342HTR
Recommended horsepower (HP PTO)	100 @ 160	100 @ 160	100 @ 160	100 @ 160	100 @ 160
Cutting width (in/po)	98" 2489	102" 2591	98" 2489	102" 2591	112" 2845
Cutting height (in/po)	41 1/8" 1045	41 1/8" 1045	48" 1219	48" 1219	48" 1219
Impeller RPM	540	540	540	540	540
Impeller diameter (in/po)	34" 864	34" 864	34" 864	34" 864	34" 864
Impeller depth (in/po)	14 1/4" 362	14 1/4" 362	14 1/4" 362	14 1/4" 362	14 1/4" 362
Number of blades	5	5	5	5	5
Impeller shaft diameter (in/po)	2" 51	2" 51	2" 51	2" 51	2" 51
Balanced impeller	Std	Std	Std	Std	Std
Drum center height (in/po)	21" 533	21" 533	21" 533	21" 533	21" 533
Removable rotary drum	-	-	- / Std	- / Std	- / Std
Chute rotation by hydraulic motor with valve (gear)	Std	Std	Std	Std	Std
Hydraulic deflector	Std	Std	Std	Std	Std
Manual deflector	Opt.	Opt.	Opt.	Opt.	Opt.
Hyd. cylinder for chute deflector (in/po)	2 1/2" X 8" 64 X 203	2 1/2" X 8" 64 X 203	2 1/2" X 8" 64 X 203	2 1/2" X 8" 64 X 203	2 1/2" X 8" 64 X 203
Semi-ind. chute (2 deflectors)	Std	Std	Std	Std	Std
Hydraulic telescopic chute	Opt.	Opt.	Opt.	Opt.	Opt.
Main auger diameter (in/po)	23" 584	23" 584	23" 584	23" 584	23" 584
Upper auger diameter (in/po)	-	-	17" 432	17" 432	17" 432
Balanced auger	Std	Std	Std	Std	Std
Reversible carbon steel blade	Std	Std	Std	Std	Std
Reversible Hardox 450 steel blade	Opt.	Opt.	Opt.	Opt.	Opt.
Reversible stainless steel blade	Opt.	Opt.	Opt.	Opt.	Opt.
Tivar blade	Opt.	Opt.	Opt.	Opt.	Opt.
Lateral blades	Opt.	Opt.	Opt.	Opt.	Opt.
Adjustable carbon steel skid shoes	Std	Std	Std	Std	Std
Adjustable Hardox 450 steel skid shoes	Opt.	Opt.	Opt.	Opt.	Opt.
Adjustable stainless steel skid shoes	Opt.	Opt.	Opt.	Opt.	Opt.
Adjustable Tivar skid shoes	Opt.	Opt.	Opt.	Opt.	Opt.
Hoses holder	Std	Std	Std	Std	Std
Storage foot	Std	Std	Std	Std	Std
Driving chain	100	100	100	100	100
Number of safety bolts	3	3	3	3	3
Bearing ductile iron casing	Std	Std	Std	Std	Std
P.T.O. shaft (Std)	T80	T80	T80	T80	T80
Box reducer 1 000 @ 540	Opt.	Opt.	Opt.	Opt.	Opt.
Adjustable hitch	Std	Std	Std	Std	Std
Hitch category (QH = quick hitch)	2, QH	2, QH	2, QH	2, QH	2, QH
Approx weight (lb/kg) - 1 auger *	2295 / 1041	2316 / 1051	2537 / 1151 2772 / 1257	2560 / 1161 2774 / 1258	2664 / 1208 2878 / 1305

\*The weight includes the chute, the rotation kit, the hydraulic cylinder for chute deflector and the PTO shaft / Specifications are subject to change without notice.