



HITCH YOUR TRACTOR TO HIGH PERFORMANCE

	N74-250HINV	N82-260HINV	N92-280HINV	N102-310HINV
Recommended horsepower (HP PTO)	74" 1880	82" 2083	92" 2337	102" 2591
Cutting width (in/mm)	28" 711	28 ½" 724	31 5/8" 803	37" 940
Cutting height (in/mm)	540	540	540	540
Impeller RPM	25" 635	26" 660	28 ½" 724	31" 787
Impeller diameter (in/mm)	9" 229	11" 279	12" 305	14 ¼" 362
Impeller depth (in/mm)	4	4	4	5
Number of blades	1 9/16" 40	1 9/16" 40	1 9/16" 40	2" 51
Impeller shaft diameter (in/mm)	Std	Std	Std	Std
Balanced impeller	14 ½" 368	14 ½" 368	16 ¼" 413	18 ½" 470
Drum center height (in/mm)	-	-	-	-
Removable rotary drum	Std	Std	Std	Std
Chute rotation by hydraulic motor	Std	Std	Std	Std
Hydraulic deflector	Opt.	Opt.	Opt.	Opt.
manual deflector	2" X 4" 51 X 102	2" X 6" 51 X 152	2 ½" X 8" 64 X 203	2 ½" X 8" 64 X 203
Cylinder for chute deflector (in/mm)	Std	Std	Std	Std
Semi Industrial chute (2 deflectors)	-	-	-	-
Hydraulic telescopic chute	17" 432	17" 432	18" 457	22" 559
Main auger diameter (in/mm)	74" 1880	82" 2083	92" 2337	102" 2591
Balanced auger	Std	Std	Std	Std
Reversible carbon steel cutting edge	Std	Std	Std	Std
Reversible Hardox 450 cutting edge	Opt.	Opt.	Opt.	Opt.
Reversible stainless steel cutting edge	Opt.	Opt.	Opt.	Opt.
Tivar cutting edge	Opt.	Opt.	Opt.	Opt.
Adjustable carbon steel skid shoes	Std	-	-	Std
Adjustable Hardox 450 skid shoes	Opt.	Opt.	Opt.	Opt.
Adjustable stainless steel skid shoes	Opt.	Opt.	Opt.	Opt.
Adjustable Tivar skid shoes	Opt.	Opt.	Opt.	Opt.
Driving chain	60	60	80	80
Number of safety bolts	2	2	2	3
Bearing ductile iron casing	Std	Std	Std	Std
PTO shaft - standard	T40 long	T60 long	T60 long	T80 long
Hitch category (QH = quick hitch)	1, 1 QH	1 & 2	2	2
Approx. weight (lb/kg) - 1 auger	934 / 424	1113 / 505	1650 / 748	2206 / 1001

The weight includes the chute, the cylinder for chute deflector, the rotation kit and the PTO shaft. Specifications are subject to change without notice.