



HITCH YOUR TRACTOR TO HIGH PERFORMANCE

	N74-260H	N82-260H N82-260HTR	N82-270H	N82-270HD	N86-270H N86-270HTR
Recommended horsepower (HP PTO)	40 @ 65	40 @ 65	40 @ 65	40 @ 75	45 @ 75
Cutting width (in/mm)	74" 1880	82" 2083	82" 2083	82" 2083	86" 2184
Cutting height (in/mm)	32 1/2" 826	32 1/2" 826	34" 864	38" 965	34" 864
Impeller RPM	540	540	540	540	540
Impeller diameter (in/mm)	26" 660	26" 660	27 1/2" 699	27 1/2" 699	27 1/2" 699
Impeller depth (in/mm)	11" 279	11" 279	11" 279	11" 279	11" 279
Number of blades	4	4	4	4	4
Impeller shaft diameter (in/mm)	1 9/16" 40	1 9/16" 40	1 9/16" 40	1 9/16" 40	1 9/16" 40
Balanced impeller	Std	Std	Std	Std	Std
Drum center height (in/mm)	15 1/2" 394	15 1/2" 394	18 3/4" 476	18 3/4" 476	18 3/4" 476
Removable rotary drum	-	- / Std	-	-	- / Std
Cylinder for chute (deflector) (in/mm)	2" X 6" 51 X 152	2" X 6" 51 X 152	2" X 6" 51 X 152	2" X 6" 51 X 152	2" x 6" 51 X 152
Chute rotation by hydraulic motor (gear with cushion valve)	Std	Std	Std	Std	Std
Hydraulic deflector	Std	Std	Std	Std	Std
Manual deflector	Opt.	Opt.	Opt.	Opt.	Opt.
Semi industrial chute (2 deflectors)	Std	Std	Std	Std	Std
Hydraulic telescopic chute	-	-	-	-	Opt.
Main auger diameter (in/mm)	19 1/2" 495	19 1/2" 495	19 1/2" 495	19 1/2" 495	19 1/2" 495
Upper auger diameter	-	-	-	-	-
Balanced auger	Std	Std	Std	Std	Std
Reversible carbon steel blade	Std	Std	Std	Std	Std
Reversible Hardox 450 blade	Opt.	Opt.	Opt.	Opt.	Opt.
Reversible stainless steel blade	Opt.	Opt.	Opt.	Opt.	Opt.
Tivar blade	Opt.	Opt.	Opt.	Opt.	Opt.
Lateral blades	Opt.	Opt.	Opt.	Opt.	Opt.
Adjustable carbon steel skid shoes	Std	Std	Std	Std	Std
Adjustable Hardox 450 skid shoes	Opt.	Opt.	Opt.	Opt.	Opt.
Adjustable stainless steel skid shoes	Opt.	Opt.	Opt.	Opt.	Opt.
Adjustable Tivar skid shoes	Opt.	Opt.	Opt.	Opt.	Opt.
Driving chain number	60	60	80	80	80
Hoses holder	Std	Std	Std	Std	Std
Storage foot	Std	Std	Std	Std	Std
Number of safety bolts	2	2	2	2	2
Bearing ductile iron casing	Std	Std	Std	Std	Std
Shaft P.T.O. standard	T60	T60	T60	T60	T60
1 000 @ 540 reducer box	-	-	-	-	-
Adjustable hitch	Std	Std	Std	Std	Std
Hitch category (QH = quick hitch)	1, 1 QH, 2	1, 1 QH, 2	1, 1 QH, 2	1, 1 QH, 2	1, 1 QH, 2
Approx. weight (lb/kg) - 1 auger *	1057 / 479	1102 / 500 1232 / 559	1159 / 526	1175 / 533	1175 / 533 1296 / 588

\*The weight includes the chute, the rotation kit, the hydraulic cylinder for chute deflector and the PTO shaft. Specifications are subject to change without notice