



	1 auger only (LP)	1 or 2 augers	1 auger only (LP)			
	N86-280H N86-280HTR	N86-282H N86-282HTR	N92-280H	N92-300H N92-300HTR	N92-300HD	N98-300H
Recommended horsepower (HP PTO)	60 @ 85	60 @ 85	60 @ 85	75 @ 120	75 @ 120	75 @ 120
Cutting width (in/mm)	86" 2184	86" 2184	92" 2337	92" 2337	92" 2337	98" 2489
Cutting height (in/mm)	36" 914	41" 1041	36" 914	38" 965	42" 1067	38" 965
Impeller RPM	540	540	540	540	540	540
Impeller diameter (in/mm)	28 ½" 724	28 ½" 724	28 ½" 724	30" 762	30" 762	30" 762
Impeller depth (in/mm)	12" 305	12" 305	12" 305	12" 305	12" 305	12" 305
Number of blades	4	4	4	5	5	5
Impeller shaft diameter (in/mm)	1 9/16" 40	1 9/16" 40	1 9/16" 40	1 ¾" 44	1 ¾" 44	1 ¾" 44
Balanced impeller	Std	Std	Std	Std	Std	Std
Drum center height (in/mm)	17 ¾" 451	17 ¾" 451	17 ¾" 451	21 ¼" 540	21 ¼" 540	21 ¼" 540
Removable rotary drum	- / Std	- / Std	-	- / Std	- / Std	-
Chute rotation by hydraulic motor (gear with cushion valve)	Std	Std	Std	Std	Std	Std
Hydraulic deflector	Std	Std	Std	Std	Std	Std
Manual deflector	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Cylinder for chute deflector (in/mm)	2 ½" X 8" 64 X 203	2 ½" X 8" 64 X 203	2 ½" X 8" 64 X 203	2 ½" X 8" 64 X 203	2 ½" X 8" 64 X 203	2 ½" X 8" 64 X 203
Semi industrial chute (2 deflectors)	Std	Std	Std	Std	Std	Std
Hydraulic telescopic chute	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Main auger diameter (in/mm)	23" 584	23" 584	23" 584	23" 584	23" 584	23" 584
Upper auger diameter	-	13" 330	-	-	-	-
Balanced auger	Std	Std	Std	Std	Std	Std
Reversible carbon steel blade	Std	Std	Std	Std	Std	Std
Reversible Hardox 450 blade	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Reversible stainless steel blade	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Tivar blade	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Lateral blades	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Adjustable carbon steel skid shoes	Std	Std	Std	Std	Std	Std
Adjustable Hardox 450 skid shoes	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Adjustable stainless steel skid shoes	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Adjustable Tivar skid shoes	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Driving chain number	80	80	80	80	80	80
Hoses holder	Std	Std	Std	Std	Std	Std
Storage foot	Std	Std	Std	Std	Std	Std
Number of safety bolts	2	2	2	2	2	2
Bearing ductile iron casing	Std	Std	Std	Std	Std	Std
Shaft P.T.O. standard	T60	T60	T60	T80	T80	T80
1 000 @ 540 reducer box	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Adjustable hitch	Std	Std	Std	Std	Std	Std
Hitch category (QH = quick hitch)	2, QH	2, QH	2, QH	2, QH	2, AR	2, AR
Approx. weight (lb/kg) - 1 auger *	1649 / 748 1790 / 812	1922 / 872 2036 / 924	1675 / 760 -	1790 / 812 1975 / 896	1790 / 812	1910 / 866 -

\* The weight includes the chute, the rotation kit, the hydraulic cylinder for chute deflector and the PTO shaft. Specifications are subject to change without notice