



HITCH YOUR TRACTOR TO HIGH PERFORMANCE

	N50-262H	N60-262H
Recommended horsepower (HP PTO)	50 @ 75	50.@ 75
Cutting width (in/mm)	50'' 1270	60'' 1524
Cutting height (in/mm)	37'' 940	37'' 940
Impeller RPM	540	540
Impeller diameter (in/mm)	26'' 660	26'' 660
Impeller depth (in/mm)	11'' 279	11'' 279
Number of blades	4	4
Impeller shaft diameter (in/mm)	1 9/16'' 40	1 9/16'' 40
Balanced impeller	Std	Std
Drum center height (in/mm)	15''	15''
Removable rotary drum	-	-
Chute rotation by hydraulic motor	Std	Std
Hydraulic deflector	Std	Std
Manual deflector	Opt.	Opt.
Cylinder for chute (deflector) (in/mm)	2'' x 6'' 51 x 152	2'' x 6'' 51 x 152
Semi industrial chute (2 deflectors)	Std	Std
Hydraulic telescopic chute	-	-
Main auger diameter (in/mm)	19'' 483	19'' 483
Upper auger diameter (in/mm)	13'' 330	13'' 330
Balanced auger	Std	Std
Revesible carbon steel blade	Std	Std
Reversible Hardox 450 steel blade	Opt.	Opt.
Reversible stainless steel blade	Opt.	Opt.
Tivar blade	Opt.	Opt.
Lateral blades	Std	Std
Adjustable carbon steel skid shoes	Std	Std
Adjustable Hardox 450 steel skid shoes	Opt	Opt
Adjustable stainless steel skid shoes	Opt.	Opt.
Adjustable Tivar skid shoes	Opt.	Opt.
Hoses holder	Std	Std
Storage foot	Std	Std
Driving chain	80	80
Number of safety bolts	2	2
Bearing ductile iron casing	Std	Std
Shaft P.T.O. standard	T60	T60
Adjustable hitch	Std	Std
Hitch category (QH = Quick hitch)	1, 1QH, 2	1, 1QH, 2
Approx. weight (lb/kg) - 1 auger	1172 / 532	1224 / 555

*The weight includes the chute, the cylinder for chute deflector, the rotation kit and the PTO
Specifications subject to change without notice