

Unverferth® Tillage

Implement Caddy



Model 700



Model 500



Put All Your Horsepower to Work!

Put all your big-tractor horsepower to work with the Unverferth Implement Caddy. The 3-point connection on models 700, 500 and 300 makes one-person hookup to virtually all 3-point equipment fast, simple and easy.

Models 700, 500 and 300

Put All Your Horsepower to Work

Big-tractor horsepower doesn't do you any good if it can't be used for all your tillage needs. The Unverferth® Implement Caddy features easy, hookup to virtually all 3-point equipment, including the Zone-Builder®, Ripper-Stripper®, Ripper-Roller and Ripper-Bedder subsoilers, and their mounted tillage attachments.



- Dual wheels for greater flotation and transport stability
- Adjustable tongue height with single-tang hitch for easily matching the tractor drawbar
- Standard transport chain
- Adjustable top link for easily leveling the attached implement
- 3,000 p.s.i. hydraulic cylinders for quickly raising and lowering unit
- Choice of powder-coat tractor-red or green finish for optimum corrosion resistance
- Electrical and hydraulic extension kits for allowing quick connection at the rear of the caddy; standard on model 700, optional on 500 and 300
- The model 700 fits up to 16-shank rippers and features:
 - Parallel axle lift arms for level, uniform lifting with up to 30" of clearance
 - 8" x 8" tubular steel axle arms for enhanced durability
 - Available with Cat. 4 narrow-hitch attachment
 - Pull-through 4" x 10" steel frame
 - Oscillating dual wheels for enhanced transport stability
- The model 500 fits up to 9-shank folding machines; the model 300 fits up to 6-shank equipment
 - Pull-through design with a fully welded tubular steel frame for maximum strength; 4" x 8" on model 500, 4" x 6" on 300
 - Cat. 3 lower quick-hitch with auto-latch attachment ; top quick link standard on model 500 and optional on model 300
 - Durable 6" x 6" tubular steel axle arms
 - Up to 34" of transport clearance



Model 300

Specifications						
Model	Dual Tire Size	Fits Machine	Lift Capacity	Width	Length	Max. H.P.
Model 700	385/65 x 22.5 163D LI	Up to 16 shanks	22,000 lbs.	14'1"	19'10"	600
	295/75 x 22.5		16,000 lbs.			
Model 500	14L x 16.1 14-ply	Up to 9 shanks	13,000 lbs.	10'7"	13'8"	500
	12.5L x 15 F-Range					
Model 300	9.5L x 15 8-Ply	Up to 6 shanks	9,000 lbs.	10'2"	13'8"	400

Due to continuing improvements in the design and manufacture of Unverferth products, all specifications contained herein are subject to change without notice.

See your nearest Unverferth dealer today or visit umequip.com for complete information on the 700, 500 and 300 Implement Caddy models.