## **BUSH HOG®**



Performance You Can Count On™

# SINGLE-SPINDLE ROTARY CUTTERS

BH200 SERIES



#### SINGLE-SPINDLE ROTARY CUTTERS

### **Bush Hog®'s Legendary Single-Spindle Rotary Cutters**

Grass, weeds, and small brush are no match for these authentic Bush Hog® built cutters. Available in 5-foot, 6-foot, and 7-foot cutting widths, the BH200 Series Rotary Cutters are designed to deliver superior performance in tough conditions, day after day, year after year.

#### BH200 Series Features ...

- Strongbacks and Gearbox Stand are located under the deck creating a smooth-top for easy cleaning
- Taller Sidebands allow more material and airflow under the deck increasing cutting volume and clipping efficiency
- 1/4" Skids run half the length of the cutter to protect the sidebands and add strength and stiffness
- Rear Band is continuously welded and curved to add strength and resist bending
- Formed Tailwheel Bracket is fully welded to the deck providing superior strength during punishing vertical and horizontal loads
- Custom Blades are forged and heat-treated to exacting standards, featuring unique Bush Hog® branding



- Smooth-top Deck makes clean-up a snap
- Gearboxes are put through the paces during customdesigned lab tests that mimic real-world conditions and obstacles like rocks and stumps, while hundreds of hours in field performance tests prove that these cutters are Bush Hog® Tough
- Quick Hitch compatibility allows for easier cutter attachment saving you time and energy
- Lower Double Hitch Lugs are welded to the strongbacks providing greater overall hitch and deck strength
- Laminated Tailwheels are puncture-proof and caster effortlessly through all kinds of terrain

SPECIFICATIONS			
MODELS	BH215	BH216	BH217
Cutting Width (in)	60	72	84
Cutting Height (in)	2 - 12	2 - 12	1 - 10
Cutting Capacity (in)	2	2	2
Hitch Type	Cat 1 Std & QH Compatible	Cat 1 Std & QH Compatible	Cat 1 or 2 Std & QH
Deck Thickness (ga)	11	10	10
Sidebands	11-1/2" x 11 ga	11-1/2" x 10 ga	11-3/4" x 10 ga
Driveline	ASAE Cat 3	ASAE Cat 3	ASAE Cat 3
<b>Driveline Protection</b>	Shearbolt or Slip-Clutch	Shearbolt or Slip-Clutch	Slip-Clutch Standard
Gearbox Rating (PTO)	65	65	130
Tractor PTO Speed	540	540	540
Minimum Tractor HP	25	30	50
Blade Holder	Oval	Oval	Oval
Blades (in)	1/2 x 4 uplift	1/2 x 4 uplift	1/2 x 4 uplift
Blade Tip Speed (FPM)	14335	14963	14963
Tires	16" Laminated	16" Laminated	16" Laminated
Safety Shielding	Front and Rear Deflectors or Chains	Front and Rear Deflectors or Chains	Front and Rear Deflectors or Chains
Approximate Weight (lbs)	655	804	1036
Warranty	6 Year Gearbox Warranty and 1 Year Limited Machine Warranty		
Color	Available in Red, Green, Orange, Blue		

