

# **BUSH HOG**<sup>®</sup>

Performance You Can Count On™

## SINGLE-SPINDLE ROTARY CUTTERS BH300 SERIES





#### BH300 SERIES SINGLE-SPINDLE ROTARY CUTTERS

### Bush Hog<sup>®</sup>'s Legendary Single-Spindle Rotary Cutters

Dense grass, tough weeds, and thick brush are no match for these authentic Bush Hog<sup>®</sup> built cutters. Available in 5-foot, 6-foot, and 7-foot cutting widths, the BH300 Series Rotary Cutters are designed to deliver superior performance in tough conditions, day after day, year after year.

#### BH300 Series Features ...

- **Strongbacks and gearbox stand** are located under the deck creating a smooth-top for easy cleaning
- **Taller Sidebands** allow more material and airflow under the deck increasing cutting volume and clipping efficiency
- **Replaceable 1/4**" **Skids** run half the length of the cutter to protect the sidebands and add strength and stiffness
- **Rear Band** is continuously welded and curved to add strength and resist bending
- Gearboxes are put through the paces during custom-designed lab tests that mimic real-world conditions and obstacles like rocks and stumps, while hundreds of hours in field performance tests prove that these cutters are Bush Hog<sup>®</sup> Tough
- **Custom Blades** are forged and heat-treated to exacting standards, featuring unique Bush Hog<sup>®</sup> branding

BUSH HOG

- Formed Tailwheel Bracket is fully welded to the deck providing superior strength during punishing vertical and horizontal loads
- **Quick Hitch** compatibility allows for easier cutter attachment saving you time and energy
- Lower Double Hitch Lugs are welded to the strongbacks providing greater overall hitch and deck strength
- Laminated Tailwheels are puncture-proof and caster effortlessly through all kinds of terrain

SPECIFICATIONS			
MODELS	BH315	BH316	BH317
Cutting Width (in)	60	72	84
Cutting Height (in)	2 - 12	2 - 12	2-12
Cutting Capacity (in)	3	3	3
Hitch Type	Cat 1 & 2 Std & QH	Cat 1 & 2 Std & QH	Cat 2 or 3 Std & QH
Deck Thickness (ga)	10	10	10
Sidebands	11-1/2" x 1/4"	11-1/2" x 1/4"	11-3/4" x 1/4"
Driveline	ASAE Cat 4	ASAE Cat 4	ASAE Cat 4
Driveline Protection	Slip-Clutch	Slip-Clutch	Slip-Clutch
Gearbox Rating (PTO)	130	130	130
Tractor PTO Speed	540	540	540
Minimum Tractor HP	35	45	55
Blade Holder	Round	Round	Round
Blades (in)	1/2 x 4 uplift	1/2 x 4 uplift	1/2 x 4 uplift
Blade Tip Speed (FPM)	14,600	15,000	14,450
Tires	16" Laminated	16" Laminated	Single or Dual 16" Laminated
Safety Shielding	Front and Rear Deflectors or Chains	Front and Rear Deflectors or Chains	Front and Rear Deflectors or Chains
Approximate Weight (lbs)	890	1,050	1,250
Warranty	6 Year Gearbox Warranty and 1 Year Limited Machine Warranty		
Color	Available in Red, Green, Orange, Blue		



Bush Hog<sup>®</sup>, Inc. 2501 Griffin Ave., Selma, AL 36703 334.874.2700 www.bushhog.com