

Post Drivers

Shaver

POWER

With models delivering up to 100,000 pounds of impact, Shaver post drivers can drive everything from steel posts, wood posts, even railroad ties into the ground.

SIMPLICITY

Shaver post drivers make it driving posts simple. Just load the driver and go. No digging, no pointing, no tamping and no setting.

SPEED

Shaver post drivers make quick work out of fence building chores, allowing you to drive a four or five inch post in as little as 10 to 15 seconds.

PILOT AUGER

The optional Shaver Pilot Auger Attachment makes post driving in the toughest soil conditions even easier. The unit's powerful 4 inch auger opens a pilot hole before driving the post. This new option reduces wear on the driver and significantly increases productivity by allowing the operator to drive posts more quickly. The unit is especially useful in tough, compacted soil conditions or when driving larger diameter posts (like railroad ties) and is available for both the HD-10 and HD-12 units.



"POSITIONER" HYDRAULIC EXTENSION UNIT

The optional "Positioner" lets you position the driver with pinpoint accuracy. A hydraulic swivel rotates the driver up to 155 degrees and extends 24 inches past the tire, making it much easier to position posts without the need to move the tractor. The unit is available for all Shaver drivers.



RELIABILITY

You can be sure that your post driver will pay for your investment in it long before it's done working for you.



SELF-CONTAINED POWER

Self-contained unit with its own hydraulic system eliminates dirt and foreign material in the operator's skid steer loader's hydraulic system.

A patented safety arm attachment holds the post in position, providing added safety for the operator.



Offset controls allow the operator to stand safely to the side of the unit while posts are being driven.



QUICK-TACH

Reduce setup time with Shaver's Quick-Tach system. With the Quick-Tach bracket, you can hook up to any skid steer loader in no time.

- Offset controls let the operator stand safely to the side of the driver.
- Rubber guard shields the operator from impact and any flying debris.
- Safety arm securely positions posts in the driving ram.
- Standard stabilizer package provides greater stability during operation.



DISTRIBUTED BY:



www.walcoequipment.com

HEAD OFFICE

20 ARTHUR STREET NORTH, ELMIRA, ONTARIO N3B 1Z9

TEL: (519) 669-4025 FAX: (519) 669-1436

ORDER DESK

e-mail: orders@walcoequipment.com

TEL: (519) 669-1401 FAX (519) 669-3499

QUEBEC OFFICE

364 RTE. 122 ST. GERMAIN DE GRANTHAM, QUÉBEC J0C

TEL: (819) 395-5115 Fax (819) 395-2624

e-mail: walcoqc@walcoequipment.com

WALCO USA

4469 292nd St. E. Box 57 Randolph MN 55065

Tel: (507) 663-9090 Fax (507) 663-0999



FEATURES AND SPECIFICATIONS	HD-8 "The Pounder"	HD-10 "The Workhorse"	HD-12 "The Brute"
Impact at Full Stroke	30,000 lbs.	71,500 lbs.	100,000 lbs.
Effective Weight of Spring-Powered Hammer	360 lbs.	725 lbs.	1,100 lbs.
Operating Distance Above Ground	53" - 126"	53" - 128"	53" - 128"
Max. Post Width	7-1/8"	8 3/4"	10-7/8"
Max. Post Length	10 feet	10 feet	10 feet
No. of Block Studs	4	8	8
No. of Nyrin Blocks	4	8	8
Tilt	Front-back / side-side	Front-back / side-side	Front-back / side-side
With Manual Base Plate	15 degrees / 15 degrees	15 degrees / 15 degrees	N/A
With Hydraulic Base Plate	15 degrees / 15 degrees	15 degrees / 15 degrees	20 degrees / 25 degrees
4 Inch Pilot Auger Attachment	N/A	optional	optional
Category I, II or III Assembly	Cat I & II	Cat II & III	Cat II & III
Mounting	front or rear or skid loader	front or rear or skid loader	rear or skid loader
Hydraulic Requirements	3-4 gpm / 1,500 psi	12 gpm / 1,500 psi	15 gpm / 2,000 psi
Approx. Shipping Weight With Hydraulic Base Plate	486 lbs.	714 lbs.	957 lbs.
With Manual Base Plate	438 lbs.	694 lbs.	N/A
THE POSITIONERS			
	SB-02	SB-12	SB-22
Collapsed Width	66"	66"	92"
Extended Width	90"	90"	116"
Height	37 1/2" - 55 1/2"	37 1/2"	37 1/2"
Weight	705 lbs.	680 lbs.	861 lbs.
Swivel	0 - 155 degrees	0 - 155 degrees	0 - 155 degrees

DISTRIBUTED BY:



www.walcoequipment.com

HEAD OFFICE

20 ARTHUR STREET NORTH, ELMIRA, ONTARIO N3B 1Z9

TEL: (519) 669-4025 FAX: (519) 669-1436

ORDER DESK

e-mail: orders@walcoequipment.com

TEL: (519) 669-1401 FAX (519) 669-3499

QUEBEC OFFICE

364 RTE.122 ST.GERMAIN DE GRANTHAM, QUÉBEC J0C

TEL: (819) 395-5115 Fax (819) 395-2624

e-mail: walcoqc@walcoequipment.com

WALCO USA

4469 292nd St. E. Box 57 Randolph MN 55065

Tel: (507) 663-9090 Fax (507) 663-0999