

# Walco Tool Arm



- ◆ **Pendular mounting enables the cutter to follow the contour of the ground when control cylinder is in the float position.**
- ◆ **Mow ditches with down angle to 55°.**
- ◆ **Transport arm collapses to reduce stress to the arm, and also to stabilise the weight.**
- ◆ **Main lift cylinder is equipped with a pilot to operated check valve to prevent the arm from drifting in the working position, and also to retain arm safety in the transport position.**

## WTA 5-6

Weight 900 lbs.

Capacity Max. 800 lbs.

### Tractor Size Requirement

5' cutter min. 60 hp  
6' cutter min. 80 hp

Cuts @ 55° with cylinder extended  
Cuts @ 90° with cylinder retracted

Requires two remote outlets

Category 1 & 2

Pilot operated check valve to prevent drift in working position

## WTA 4

Weight 705 lbs.

Capacity max. 480 lbs.

### Tractor Size Requirement

30 hp min. to 40 hp max.  
Minimum tractor weight – 3600 lbs.  
Front counter-weights are required  
Maximum cutter width: 4'

Cuts @ 55° with cylinder extended  
Cuts @ 90° with cylinder retracted

Requires two remote outlets

Category 1

Pilot operated check valve to prevent drift in working position



[www.walcoequipment.com](http://www.walcoequipment.com)

#### HEAD OFFICE

20 ARTHUR STREET NORTH, ELMIRA, ONTARIO N3B 1Z9  
TEL: (519) 669-4025 FAX: (519) 669-1436

#### ORDER DESK

e-mail: [orders@walcoequipment.com](mailto:orders@walcoequipment.com)  
TEL: (519) 669-1401 FAX (519) 669-3499

#### QUEBEC OFFICE

364 RTE.122 ST.GERMAIN DE GRANTHAM, QUÉBEC JOC  
TEL: (819) 395-5115 Fax (819) 395-2624  
e-mail: [walcoqc@walcoequipment.com](mailto:walcoqc@walcoequipment.com)

#### WALCO USA

4469 292<sup>nd</sup> St. E. Box 57 Randolph MN 55065  
Tel: (507) 663-9090 Fax (507) 663-0999