## REAR DISCHARGE FINISHING MOWER



## A CUT ABOVE THE REST.

Available in cutting widths of 60, 72, and 84 inches, the RDTH Series is designed to deliver a smooth, even cut with the superior distribution of rear discharge. Floating top and lower links allow for a uniform cut on uneven terrain and high blade tip speeds prevent streaking. Cutting height is easily adjustable from 1 to 6 inches. The closed box design and heavy rear discharge chain shielding reduces potential damage from thrown rocks and other debris.

## Smooth, even cut with the superior distribution of rear discharge

- 60- to 84-inch cutting widths
- For 15 to 55+ HP tractors
- Designed to deliver the quality distribution of rear discharge
- Floating top and lower links for uniform cut on uneven terrain
- High (18,000 plus FPM) blade tip speed prevents streaking
- Bush Hog® field proven spindles
- Single Aramid Cord reinforced belt

- Easy-to-use grease zerk in caster stem
- Spring-loaded idler adjusts belt tension
- Rear chains standard on RDTH-60 and RDTH-72
- Flared deck design on RDTH-84
- Easy cutting height adjustment from 1 to 6 inches
- 7-gauge steel deck

SPECIFICATIONS			
MODEL	RDTH-60	RDTH-72	RDTH-84
Cutting Width	60 inches	72 inches	84 inches
Cutting Height (1/2 inch increments)	1-1/2 to 6-1/2 inches	1-1/2 to 6-1/2 inches	1-1/2 to 5-1/2 inches
Tractor HP Range	15 - 35 PTO	20 - 40 PTO	30 - 55 PTO
Type Hitch	Category I	Category I	Category I
Size Blades	1/4 x 2.5 x 21 inches	1/4 x 2.5 x 25 inches	5/16 x 2.5 x 29 inches
Number of Blades	3	3	3
Blade Tip Speed	18,231 FPM	18,272 FPM	18,475 FPM
Blade Overlap	1-1/2 inches	1-1/2 inches	1-1/2 inches
Blade Uplift	Parallel	Parallel	Parallel
Driveline Size	ASAE Category 3	ASAE Category 3	ASAE Category 3
Front Roller Size (optional)	3 x 5 inches	3 x 5 inches	3 x 13 inches
Discharge	Rear	Rear	Rear
Deck Plate	7 gauge	7 gauge	7 gauge
Tire Size	3-1/4 x 10-1/4 inches	3-1/4 x 10-1/4 inches	4 x 10 inches
	(solid tire)	(solid tire)	(solid tire)
Belt	"B" size Aramid Cord	"B" size Aramid Cord	"B" size Aramid Cord
Gearbox	45 HP	45 HP	55 HP
Tractor PTO Speed	540 RPM	540 RPM	540 RPM
Belt Adjustment	Spring Loaded Idler	Spring Loaded Idler	Spring Loaded Idler
Approx. Weight	536 lbs.	588 lbs.	874 lbs.
Options	Front Roller Kit	Front Roller Kit	Front Roller Kit
Warranty	1-year limited warranty with a 5-year gearbox limited warranty		



2501 Griffin Ave. Selma, Alabama 36703

Tel: 800-363-6096 Fax: 334-874-2701 www.bushhog.com

Bush Hog and (hog icon) are registered trademarks of Alamo Group Inc. Copyright © 2017