BUSH HOG®



Performance You Can Count On™

BACKHOES

XDSERIES | XD65C, XD65, XD75, XD95, XD95EL, XD600S









BACKHOES



With a digging depth of 6 feet and an 8-foot reach, the XD65 gets down and dirty, breaking the frostline and finishing the job quickly.

Digging 7.5 feet deep and reaching 10 feet across, the XD75 breaks ground and keeps on going. With an excavator-style curved boom and easy-to-use controls, the XD75 is ready to handle any ground conditions from topsoil to clay and gravel. becomes quick and easy without the added expense of a single-purpose excavator. The digging bucket is built using AR400-strength steel, ensuring rugged longevity.

Break ground, not your back!

Easily access those tight work spaces and get down to some digging. Bush Hog®'s new line of XD series backhoes are designed for tractors ranging from 18 to 100 horsepower along with skid steers and mini skid steers depending on the model. Perfect for digging footers, trenches and all general landscaping and construction needs, the XD series backhoes deliver value and strong performance to your operation.

Built To Last.





The Bush Hog® digs even deeper with the Extendable XD95EL model. Capable of hydraulically extending an extra 24" to dig 11' 4" deep, the extendable dipper stick gives you the extra reach when you need it. When contracted, the bucket and dipper stick curl up tight to the boom for easy travel and compact storage.



Xtreme Digger Skid Steer 6'

When you need to get down to work, start digging with the Bush Hog® XD600S. This skid steer-mounted backhoe is a single-stick that reaches 6 feet deep and is controlled from inside the cab. The XD600S keeps you trenching without the need of continually repositioning.

SPECIFICATIONS					
Model	XD65C	XD65	XD75	XD95	XD95EL
Transport Height (with boom fully retracted)	64.5"	63"	79"	92"	92"
Transport Width (with stabilizers up)	41"	40"	42½"	42½"	42½"
Loading Height (bucket at 60° rotation)	62"	62"	80"	89"	89"/104"
Ground Clearance	8½"	10½"	10½"	10½"	10½"
Transport Length	56"	68"	80"	81"	81"
Transport Weight (base unit only - no bucket or mounts)	500 lbs.	575 lbs.	800 lbs.	850 lbs.	1000 lbs.
Digging Depth (2 ft. flat bottom)	6'4"	6'4"	7'8"	9'4"	9'4"/11'4"
Overall Operating Height (fully raised)	91"	92"	119"	135"	135"/152"
Reach from Swing Post	100"	100"	123"	141"	141"/164"
Bucket Rotation	180°	180°	180°	180°	180°
Swing Arc	150°	180°	180°	180°	180°
Stabilizer Width (Spread)	72"	74"	89"	89"	89"
Stabilizer Width (Transport)	41"	40"	42½"	42½"	42½"
Operating Pressure	1800 psi	1800 psi	2250 psi	2250 psi	2250 psi
SAE* Dipper Boom Digging Force	1250 lbs.	1250 lbs.	2300 lbs.	3200 lbs.	3100/2200 lbs.
SAE* Bucket Digging Force	2054 lbs.	2600 lbs.	3800 lbs.	3925 lbs.	3925 lbs.
Boom Lift Capacity (end of dipper 3' from ground)	250 lbs.	385 lbs.	925 lbs.	750 lbs.	710/580 lbs.
Hydraulic Volume Requirements	3½-6 gpm*	5-7 gpm*	5-7 gpm*	5-7 gpm*	5-7 gpm*
Flow Divider	-	-	Included	Included	Included
Recommended Tractor HP	18-28 HP	18-30 HP	30-60 HP	45-100 HP	45-100 HP
Recommended Skidsteer Requirements	Mini Skidsteer	Mini Skidsteer	30-60	45-100	45-100
Cylinder Diameters Main Boom Cylinder Diameter	2.5	2.5	3.0	3.0	3.0
Dipper Cylinder Diameter	2.25	2.25	2.5	2.5	2.5
Bucket Cylinder Diameter	2.5 (x1)	2.0 (x2)	2.5 (x2)	2.5 (x2)	2.5 (x2)
Swing Cylinder Diameter	2	2.25	2.5	2.5	2.5
Stabilizer Cylinder Diameter	2	2.0	2.5	3.0	3.0
Extender Cylinder Diameter	-	-	-	-	1.75
Bucket Sizes Available	9, 12, 15, 18	9, 12, 15, 18	9, 12, 15, 18, 24	9, 12, 15, 18, 24	9, 12, 15, 18, 24
3 Point Hitch	n/a	Cat I (PT300)	Cat I (PT300) / Cat II (PT322)	Cat I (PT300) / Cat II (PT322)	Cat I (PT300)/ Cat II (PT322)

Bush Hog uses Pioneer style ball type hydraulic couplings for all tractor auxiliary connections. Substitutions must be made at the customers expense. Bush Hog backhoes are designed for two line open center hookup.



2501 Griffin Ave.Selma, Alabama 36703Tel: 800-363-6096

Fax: 334-874-2701 www.bushhog.com

Bush Hog and (hog icon) are registered trademarks of Alamo Group Inc. Copyright © 2017