



# SNOWBLOWERS DOUBLE AUGER

## STANDARD FEATURES

- ◆ 4 bladed fan
- ◆ Shear bolt protection
- ◆ Greaseable bearings
- ◆ Heavy augers and shafts
- ◆ Orbital motor chute rotator
- ◆ Single section spout deflector
- ◆ Heavy duty PTO with needle bearings
- ◆ Heavy duty gearbox with heat treated gears and tapered roller bearings

## OPTIONS

- ◆ Skid shoes
- ◆ Quick hitch set-up
- ◆ Weld on cutting edge
- ◆ Reinforced endplates
- ◆ 3-section spout deflector
- ◆ Telescopic truck loading chute
- ◆ Cylinder with hoses and fittings
- ◆ Reversible bolt-on cutting edge
- ◆ 1,000 rpm (not available on D7 model, standard on D9 & D10 models)

Helm Welding (1983) Limited

## Specification Table (Double Auger Snowblowers)

MODEL SIZE	D7	D75	D8	D85	D9	D10
Weight	1195	1530	1545	1735	2130	3220
Cutting Width	84	90	96	102	108	120
Cutting Height	36	36	36	36	36	44
Fan Shaft Diameter	40 mm	1 ¾	1 ¾	2	2	2
Fan Blades	4	4	4	4	4	6
Fan Diameter	28	28	28	30	32	34
Fan Housing Width	8	12	12	12	12	12
Fan Housing (thickness)	10 ga.	3/16	3/16	3/16	3/16	3/16
Auger Diameter	17	17	17	17	17	20
Auger Shaft Diameter	1 7/16	1 7/16	1 7/16	1 7/16	1 7/16	1 3/4
Auger Flighting Thickness	½	½	½	½	½	½
Auger Chain Size	#60	#80	#80	#80	#80	#80
Chute Diameter	12	13	13	13	13	15
Chute Length	36	48	48	48	48	48
Orbital Motor Chute Rotator	Stan.	Stan.	Stan.	Stan.	Stan.	Stan.
Spout Deflector (Single)	Stan.	Stan.	Stan.	Stan.	Stan.	Stan.
Hitch Category	1 & 2	2	2	2	2	2
Recommended H.P. (min)	70	80	90	100	120	140
(max)	90	105	115	150	160	180

H.P. recommendations are suggested only (pending snow and ground speed conditions and transmission type)  
 Unless otherwise indicated, all dimensions are in inches with standard equipment installed.  
 Specifications subject to change without notice.  
 Certain features shown may be optional.