



GRAIN BUGGIES

STANDARD FEATURES

- ◆ Safety chains
- ◆ Hydraulic hoses
- ◆ Left side extension
- ◆ Spot light on auger
- ◆ Light bar kit with 30' cord
- ◆ Bottom of hopper pit door
- ◆ Heavy duty unloading auger
- ◆ Heavy duty square tube axle
- ◆ Heavy duty PTO with slip clutch
- ◆ Unloading auger bottom clean out
- ◆ Heavy duty trailer jack (18,000 lb.)
- ◆ Mounting provisions for roll over tarp
- ◆ Hydraulic operated shut offs to prevent no load start ups
- ◆ Large tractor type tires (traction or all weather) to give maximum floatation for all weather conditions

OPTIONS

- ◆ Paint colours
- ◆ Roll over tarp
- ◆ 5" or 6" spindles
- ◆ Various tire sizes
- ◆ 3 bar Digi-Star scale system

Helm Welding (1983) Limited

Grain Buggy Specification Table

MODEL SIZE	412	616	816
Drag Auger	9"	12"	12"
Unloading auger	12"	16"	16"
Unloading auger height	15'-4"	16'-4"	17'
Tank width	8'	8'	10'
Tank length	15'	19'	19'
Left hand side extension (15")	standard	standard	standard
Tire size	23.1 x 26	30.5 x 32	30.5 x 32
Overall Weight (empty)	8,500 lbs.	10,800 lbs.	-
Overall Tongue Weight (empty)	2,000 lbs.	2,400 lbs.	-
Overall capacity (standard)	400 bu.	600 bu.	800 bu.
Overall capacity (with optional extension)	450 bu.	675 bu.	900 bu.
Overall Height (pending tire size)	9'	10'	10.5'

Unless otherwise indicated, all dimensions are in inches with standard equipment installed.
 Specifications subject to change without notice.
 Certain features shown may be optional.