



	CM109	CM209	CM212
DIMENSIONS			
Transport Width	172 in. (4.4 m)	172 in. (4.4 m)	184 in. (4.7 m)
Transport Length	231 in. (5.9 m)	264 in. (6.7 m)	264 in. (6.7 m)
Transport Height	54 in. (1.4 m)	63 in. (1.6 m)	63 in. (1.6 m)
WEIGHT			
Base Unit - Tractor Hydraulics	2880 lbs. (1306 kg)	3320 lbs. (1505 kg)	3860 lbs. (1751 kg)
Base Unit - Self-Contained Hydraulics	3380 lbs. (1533 kg)	3780 lbs. (1714 kg)	4320 lbs. (1960 kg)
PICKUP			
Width	108 in. (2.7 m)	108 in. (2.7 m)	144 in. (3.7 m)
Type	Spliced Belt w/Plastic Fingers	Spliced Belt w/Plastic Fingers	Spliced Belt w/Plastic Fingers
Pickup Tooth Type	Replaceable 3 Prong, Plastic	Replaceable 3 Prong, Plastic	Replaceable 3 Prong, Plastic
Separate Belt Sections	3 x 3 ft. (0.9 x 0.9 m)	3 x 3 ft. (0.9 x 0.9 m)	4 x 3 ft. (1.2 x 0.9 m)
Adjustable Pickup and Conveyor Speed			
Tractor Driven	Tractor Remote Flow Control	Tractor Remote Flow Control	Tractor Remote Flow Control
Self-Contained	Tractor PTO Speed	Tractor PTO Speed	Tractor PTO Speed
Floating Pickup	Standard, On Gauge Wheels	Standard, On Gauge Wheels	Standard, On Gauge Wheels
Lift System	Hydraulic	Hydraulic	Hydraulic
Drive Type	Hydraulic	Hydraulic	Hydraulic
Roller Windguard	N/A	Standard	Standard
CROSS CONVEYOR			
Width	42 in. (1.1 m)	42 in. (1.1 m)	42 in. (1.1 m)
Length	170.8 in. (4.3 m)	175.5 in. (4.5 m)	175.5 in. (4.5 m)
Drive Type	Hydraulic	Hydraulic	Hydraulic
Belt Type	Spliced	Spliced	Spliced
Discharge Side	Right (Left to Invert Only)	Right (Left to Invert Only)	Right (Left to Invert Only)
MERGING CAPABILITY			
Width of cut, Base Unit	9 to 12 ft. (2.7 to 3.7 m)	9 to 12 ft. (2.7 to 3.7 m)	9 to 12 ft. (2.7 to 3.7 m)
Width of cut, 2 ft. (0.6 m) Extension	11 to 14 ft. (3.4 to 4.3 m)	9 to 14 ft. (2.7 to 4.3 m)	9 to 14 ft. (2.7 to 4.3 m)
Width of cut, 4 ft. (1.2 m) Extension	N/A	9 to 16 ft. (2.7 to 4.9 m)	9 to 16 ft. (2.7 to 4.9 m)
Width of cut, 6 ft. (1.8 m) Extension	N/A	9 to 18 ft. (2.7 to 5.5 m)	9 to 18 ft. (2.7 to 5.5 m)
FRAME AND TONGUE			
Type Pull	Center	Side	Side
Tongue Swing	N/A	Hydraulic	Hydraulic
Ground Clearance - Pickup Raised	10 in. (254 mm)	11.75 in. (298 mm)	11.75 in. (298 mm)
Recommended Operating Speeds	2 to 12 mph (3.2 to 19.3 k/h)	2 to 12 mph (3.2 to 19.3 k/h)	2 to 12 mph (3.2 to 19.3 k/h)
Maximum Transport Speed	30 mph (32 k/h)	30 mph (32 k/h)	30 mph (32 k/h)
Wheels and Tires (# of tires)	(3) 6.70 x 15	(1) 6.70 x 15, (2) 9.5L x 15	(1) 6.70 x 15, (2) 9.5L x 15

TRACTOR REQUIREMENTS	
Hydraulic Flow Requirements	
With Tractor Hydraulics	16 gpm @ 2000 psi (61 lpm @ 138 bar)
With Self-Contained Hydraulics	5 gpm @ 2000 psi (19 lpm @ 138 bar)
Hydraulic Remotes Required	2 w/Tractor Driven, 1 w/Self-Contained
Hydraulic Remote Valve Type	
With Tractor Hydraulics	Double Acting with Detent and Flow Control on 1
With Self-Contained Hydraulics	Single or Double Acting
Minimum Tractor HP Recommended	70 HP (52 kW)
Seven Pin Light Connector	Required

STANDARD EQUIPMENT	
Clevis Hitch	
Parking Jack	
Pickup Gauge Wheels	
Transport Lock for Pickup	
Transport Chain	
SMV Emblem	

OPTIONAL EQUIPMENT	
CM109	
Windrow Inverter Attachment	
2 ft. Conveyor Extension	
CM209 and CM212	
Windrow Inverter Attachment	
2 ft. Conveyor Extension	
4 ft. Conveyor Extension	
6 ft. Conveyor Extension	
Cross Conveyor Extension Shut-off	



Safety Never Hurts!™ Always read the Operator's Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided.

CNH America LLC reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice.

Case IH is a registered trademark of CNH America LLC.

Any trademarks referred to herein, in association with goods and/or services of companies other than CNH America LLC, are the property of those respective companies.

Availability of some models and equipment builds vary according to the country in which the equipment is used.