

COMPACT FARMALL® A SERIES TRACTOR SPECIFICATIONS

CASE IH
AGRICULTURE



COMPACT FARMALL® A SERIES TRACTOR SPECIFICATIONS



Case IH compact Farmall A tractors provide the absolute best value for the dollar. These rugged, economical tractors tackle tough chores, from loading and mowing to rotary cutting and clearing snow.

- 3-cylinder turbo diesel Tier 4 B/Final-compliant engines deliver rapid response with low emissions.
- Roomy, open platform provides great visibility and the controls are straight-forward and easy to use.
- Choice of the smooth-shifting 12x12 transmission or a three-range, two-pedal hydrostatic transmission for infinitely variable speeds.
- High-capacity 8.2 GPM hydraulic pump plus a separate steering pump means you have generous flow for hydraulic demands.
- Full-function 3-point hitch and PTO options let you easily attach and use a wide variety of implements.
- Add the L340A front loader to expand the versatility of compact Farmall A tractors to moving soil, gravel, mulch, snow, bales and more.
- Compact Farmall A tractors are economical to buy and to use and are fully supported by your Case IH dealer.

MODEL	Compact Farmall 30A	Compact Farmall 35A
ENGINE		
Engine Type	ISM diesel, Tier 4 B/Final	
Gross HP at 2600 RPM Rated Speed	32.2 HP (24 kW)	36.2 HP (27 kW)
PTO HP @ 540 RPM	25.8 HP (19.2 kW) – Hydrostatic transmission; 27.4 HP (20.4 kW) – Gear transmission	29.0 HP (21.6 kW) – Hydrostatic transmission; 30.7 HP (22.9 kW) – Gear transmission
Number of Cylinders / Displacement / Aspiration	3 / 92 cu. in. (1.5 L) / Turbo	
Emission and Exhaust Treatment	Internal exhaust gas recirculation (EGR) plus Diesel Particulate Filter (DPF)	
Fuel Tank Capacity	7.4 U.S. gal. (28 L)	
System Rating / Alternator Rating	12 volt / 85 amp	
TRANSMISSION		
Type - Mechanical / Hydrostatic / Drive wheels	12x12 / 3-range / 4WD	
Maximum Forward Speed - Gear	14.2 MPH (22.9 Km/h)	
Maximum Forward Speed - Hydrostatic	14.8 MPH (23.8 Km/h)	
Gear Shuttle Type	Synchro	
Rear Diff. Lock Engagement	Mechanical	
Brake Type	Wet multi disc	
Creeper Range	N/A	
PTO – Rear	Independent with electro-hydraulic engagement	
Mid-Mount PTO	2,000 RPM; dealer installed attachment	
HYDRAULIC SYSTEM		
Hydraulic System Type	Open center	
Implement Pump Flow	8.2 GPM (31 L/min.)	
Number of Remotes	0 or 1	
Steering	Hydrostatic	
3-POINT HITCH		
Type	CAT I with fixed link ends, turnbuckle lift link, and telescopic stabilizers	
Lift Capacity at Lift Pin	1,808 lbs. (820 kg)	
DRAWBAR		
3-position	Extendable	
DIMENSIONS		
Length	10.08 ft. (3.07 m)	
Height	7.3 ft. (2.23 m)	
Width	5.54 ft. (1.7 m)	
Weight with ROPS	3,067 lbs. (1 391 kg)	
TIRES		
Standard	Front: 25x8.5-14, R4; Rear: 43x16.00-20, R4	
Optional	R-3 turf type and R-1 ag type	

CNH Industrial America LLC reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice. Availability of some models and equipment builds varies according to the country in which the equipment is used.

©2015 CNH Industrial America LLC. All rights reserved. Case IH is a trademark registered in the United States and many other countries, owned by or licensed to CNH Industrial N.V., its subsidiaries or affiliates. Printed in U.S.A. www.caseih.com

CIH12161501