

ROTARY CUTTER

**Farm King**

Flex-Wing Model 1530





## ROTARY CUTTER

### PRODUCT OVERVIEW

Built to clear rough areas where stones, tree stumps and debris are hidden by weeds

Double swivel clevis hitch

65 hp required

### FEATURES

Independent wheel assembly suspension

Heat-treated blades

Chain kit

### OPTIONS

Double axle

### AVAILABLE COLORS



# FLEX-WING ROTARY CUTTER

## MODEL 1530

### DECKS

The decks on this heavy-duty cutter, designed by Farm King from the ground up, are manufactured using 7 gauge steel. A deck protection ring minimizes stress on the deck while the stump jumper protects the mower deck and allows the assembly to glide over uneven terrain. The streamline deck design maintains strength and prevents buildup. Standard equipment such as a single chain guard attached to the entire deck limits the possibility of flying debris.

### SUSPENSION

The suspension on the Farm King 1530 individually isolates each wheel assembly from the machine, reducing road vibration and terrain roughness. This provides a smoother ride and reduces shock stress on the frame, axle and driveline.

### HEAT-TREATED BLADES

Each blade is heat-treated to enhance rigidity, while the heavy-duty gearbox is designed to be rugged and durable. The access panel located on the deck makes it easy to inspect, clean or replace the blades if necessary. The blades also have an industry-leading 7" overlap to make sure you get the best cut the first time.

### CUTTING WIDTH & TRANSPORT

The Farm King 1530 features an 186" cutting width in the working position and folds to only 96" for transport.

### OPTIONAL EQUIPMENT

Several options are available to enhance the Farm King 1530 to properly suit the needs of your land including light kits, double axle and either laminated or aircraft tires.



## THE NEW FARM KING 1530 ROTARY CUTTER IS DESIGNED FOR THE TOUGHEST CUTTING JOBS IN HEAVY, THICK GRASS AND WEEDS.

With a class-leading 7" blade overlap for a thorough cut and a working range of +/- 25°, this machine is ideal for cutting deep grassy ditches and trenches.

**[1]** Decks are manufactured using 7 gauge steel **[2]** The suspension individually isolates each wheel assembly from the machine, reducing road vibration and terrain roughness **[3]** Heat-treated blades for enhanced rigidity **[4]** 96" transport width



### STANDARD FEATURES

- Single chain guard
- Deck protection ring
- Stump jumper
- Transport lock / Safety chain
- 540 RPM or 1000 RPM

### OPTIONAL FEATURES

- Double axle
- Light kit
- Laminated or aircraft tires

### SPECIFICATIONS

#### MODEL >>

#### 1530

Manufacturing	Heavy-duty / Commercial	
Width, working / overall	186 in (4.7 m) / 194 in (4.9 m)	
Transport, width / height	96 in (2.4 m) / 92 in (2.3 m)	
Working range	+/- 25°	
Cutting height	2 to 15 in (51 to 381 mm)	
Weight	5900 lb (2676 kg)	
Tongue weight	2100 lb (953 kg)	
Tractor hp requirement, min.	65 hp	
Gearbox hp: splitter / wings	250 hp / 190 hp	
Gearbox speed	540 RPM	1000 RPM
Wing blade tip speed	16,481 ft/min (5023 m/min)	16,737 ft/min (5101 m/min)
Center blade tip speed	16,197 ft/min (4937 m/min)	15,802 ft/min (4816 m/min)
Blade overlap	7 in (177 mm)	
Blade	0.5 x 4, Uplift	
Stump jumper	Symmetric die pressed (7 Ga.)	
Deck material thickness	0.179 in (7 Ga) (4.5 mm)	
Side skirt thickness	0.25 in (6.4 mm)	
Side skid	Reversible and replaceable	
Suspension	Independent rubber-isolated wheel assemblies	
Hitch	Double swivel clevis hitch	
Tires	(6 in or 8 in.): 24 x 7.7 x 10 aircraft tires (air filled) or 21 in. laminated wheels (solid rubber)	



[www.farm-king.com](http://www.farm-king.com)



# Farm King

**For more information contact:**

E-mail: [info@buhler.com](mailto:info@buhler.com)

[www.farm-king.com](http://www.farm-king.com)

Equipment shown is subject to change without notice. ©2015 Buhler Trading Inc.  
Printed in Canada. TSX:BUI Ref: 062015-500-LM

**bühler** | a division of Buhler Industries Inc.