

Rotary Cutter

SERIES	I		II			
	MODEL	410	510	510	620	720
Cutting width		48"	60"	60"	72"	84"
Cutting height		Minimum 3"	Minimum 4"	Minimum 4"	Minimum 4"	Minimum 4"
Blade tip speed		13,098 ft/min	12,721 ft/min	12,721 ft/min	14,758 ft/min	14,283 ft/min
Spring steel blades		1/2" x 3" heat treated	1/2" x 3" heat treated	1/2" x 3" heat treated	1/2" x 3" heat treated	1/2" x 3" heat treated
Deck material		11 gauge	11 gauge	10 gauge	10 gauge	10 gauge
Gearbox		Closed (540 RPM)	Closed (540 RPM)	Closed (540 RPM)	Closed (540 RPM)	Closed (540 RPM)
Gearbox rating		30 hp	40 hp	40 hp	60 hp	65 hp
Tractor requirement		20 - 45 hp	25 - 55 hp	25 - 65 hp	35 - 65 hp	45 - 75 hp
PTO shaft		Shear pin	Shear pin	Shear pin	Slip clutch	Slip clutch
3-point hitch*		Category I	Category I	Category I	Category II	Category II
Tire - 3-point		15" laminated	15" laminated	16" solid rubber	16" solid rubber	20" solid rubber
Tire / wheels - trailing		N/A	N/A	Solid rubber or 15" rim	Solid rubber or 15" rim	15" rim
Stump-jumper		N/A	N/A	24" diameter	24" diameter	24" diameter
Parking jack		N/A	N/A	Optional	Optional	Optional
Chain kit		Optional	Optional	Optional	Optional	Optional
Weight - 3-point		450 lb	520 lb	601 lb	777 lb	989 lb
Weight - trailing		N/A	N/A	686 lb	856 lb	1080 lb