

WR201 & WR302 SERIES TRAILING WHEEL RAKES SPECIFICATIONS



WR201 & WR302 SERIES TRAILING WHEEL RAKES SPECIFICATIONS

MODEL	WR201	WR201	WR302	WR302	WR302
Number of Rake Wheels	8-Wheel	10-Wheel	12-Wheel	14-Wheel	16-Wheel
Rake Type	Folding V-Type Wheel Rake				
DIMENSIONS					
Overall Transport Length	21.8 ft. (6.6 m)		24.8 ft. (7.58 m)	32.8 ft. (9.96 m)	
Transport Height (with 60" Wheels)			6.4 ft. (1.95 m)		
Overall Transport Width			8.4 ft. (2.55 m)		
Maximum Working Width	17.4 ft. (5.3 m)	20.3 ft. (6.2 m)	25 ft. (7.6 m)	28.5 ft. (8.7 m)	31 ft. (9.4 m)
Minimum Windrow Width			3 ft. (0.9 m)		
Maximum Windrow Width			6 ft. (1.8 m)		
Operating Weight	2,425 lbs. (1 100 kg)	2,750 lbs. (1 247 kg)	3,700 lbs. (1 680 kg)*	5,020 lbs. (2 280 kg)*	5,285 lbs. (2 400 kg)*
RAKING COMPONENTS					
Rake Wheel Diameter	55 in. (1.4 m)		55 in. (1.4 m) – standard or 60 in. (1.52 m) – optional		
Number of Tines per Wheel			40		
Wheel Tine Diameter (55" Wheel/60" Wheel)	9/32 in. (7 mm)		9/32 in. (7 mm) on 55" wheel/19/64 in. (7.5 mm) on 60" wheel		
Wheel Hub Bearing Type	Greaseable, heavy-duty tapered roller bearings				
Wheel Spacing (Center-to-Center)	30.8 in. (780 mm)				
Ground Pressure Adjustment	Individually adjustable with single pin adjustment for all raking wheels per side				
Fixed Rear Wheel	2 - Standard				
Caster Wheels w/Adjustable Friction Discs	2 - Standard		4 - Standard		
Windrow Width Adjustment (Standard/Optional)	Mechanical ratchet turnbuckle/NA		Mechanical ratchet turnbuckle/hydraulic opening kit operated from tractor cab		
TRACTOR REQUIREMENTS					
Minimum Tractor Horsepower Required**	30HP (22 kW)		40HP (30 kW)		
Hydraulic Remotes Required	2		2 - Standard; 3 with hydraulic rear opening kit		
Tractor Electrical Requirements	7-pin light connector				
Tractor Hitch Type	Single drawbar preferred				
STANDARD EQUIPMENT					
Mechanical Transport Fold Safety Locks	Standard				
Hitch Jack	Standard				
Highway Transport Chain	Standard				
Transport Tire Quantity & Size	Four 205/75-15 in.			Six 205/75-15 in.	
OPTIONAL EQUIPMENT					
Diameter: Center Kicker Wheel	Available/44 in. (1.11 m)				
Transport Lighting Package	Available		Standard		
Single-Side Opening Kit	Available				
3rd Wheel Kit w/Tires	N/A		Available	N/A	N/A
Conversion Kit- 8-Wheel Rake to 10-Wheel	Available	N/A	N/A	N/A	N/A
Conversion Kit- 14-Wheel Rake to 16-Wheel	N/A		N/A	Available	N/A
Rear Tandem Kit w/Tires	N/A		Available		
Poly Wind Shields for Raking Wheels	Available through Parts				

Work with your dealer to configure a wheel rake perfect for your operation.

* With 60 in. wheels

** Depending on crop conditions, field conditions and weight of the tractor

Specifications are subject to change without notice. CNH Industrial America LLC reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice. Availability of some models and equipment builds varies according to the country in which the equipment is used. ©2015 CNH Industrial America LLC. All rights reserved. Case IH is a trademark registered in the United States and many other countries, owned by or licensed to CNH Industrial N.V., its subsidiaries or affiliates. CIH10021501