

# EP2500



- Easy-starting, fuel-efficient and low-emission Honda GX160H1 OHV, commercial-grade engine
- 2300 watts rated (19.2 amps)
- 14.5 L (3.2 gal imp.) fuel tank, larger than most of the competition
- Light construction, camping, boating, street vendors, operating lights, stand-by power source



## SPECIFICATIONS

GENERATOR TYPE	BRUSH TYPE	TRANSPORT WHEELS	TBA
MAXIMUM AC OUTPUT (WATTS)	2500	LIFTING HOOK	N/A
VAC VOLTAGE AVAILABLE	120	BATTERY	N/A
MAXIMUM CONTINUOUS AC OUTPUT (WATTS)	2300	APPROXIMATE RUNNING TIME / TANKFUL (HRS.)	10.2 @ Rated Load / 15.3 @ ½ Load
MAX. RATED AC AMPERAGE @ 120 V / 240 V	19.2 / -	RATED FUEL CONSUMPTION (LITRES / HOUR)	1.42**
GROUND FAULT CIRCUIT INTERRUPTER (GFCI)	N/A	NOISE LEVEL dB(A) (1.5 METRES TO 7 METRES)	69**
FREQUENCY (HERTZ)	60	LENGTH	N/A
AUTOMATIC VOLTAGE REGULATOR	STD.	LENGTH - WITH HANDLES FOLDED	N/A
DC OUTPUT (VOLTS / AMPS)	N/A	LENGTH - WITH HANDLES	N/A
Honda ENGINE	Honda GX160H1	WIDTH - WITHOUT HANDLES AND WHEELS	435 MM (17.1 IN.)
TYPE	OHV; 4-STROKE; AIR-COOLED	WIDTH - WITH WHEELS	N/A
DISPLACEMENT	163 CC	HEIGHT - WITHOUT LIFT-HOOK	437 MM (17.2 IN.)
STARTING SYSTEM	MANUAL RECOIL	HEIGHT - WITH LIFT-HOOK	N/A
LOW LEVEL OIL ALERT™ SYSTEM	STD.	DRY WEIGHT	45 KG (99.2 LB.)
AUTO THROTTLE	N/A	LENGTH - WITHOUT HANDLES AND WHEELS	597 MM (23.5 IN.)
REMOTE START CAPABILITY	NO	LENGTH - WITH HANDLES AND WHEELS	N/A
REMOTE START KIT PART NUMBER INFO	N/A	WIDTH - WITH HANDLES AND WHEELS	N/A
FUEL TANK CAPACITY (LITRES)	14.5	COMMON DUPLEX RECEPTACLE SPECIFICATIONS	19.2 amps / 120 volts continuous is available as combined total from these two A
		COLD CLIMATE TECHNOLOGY	YES

Models and/or colours may not be exactly as shown. Errors and omissions excepted. Specifications are subject to change without notice.

See your Honda Power Equipment dealer for details.

For optimum performance and safety, please read your owner's manual before operating your Honda product. Always wear the appropriate safety gear when operating your Honda.

©/TM — Trademarks of Honda Canada Inc. or used under licence from Honda Motor Co., Ltd. or third parties.