

9412 THREE-POINT MOUNTED DRILL

A Genuine Three-Point, No-Till Machine

The Sunflower Model 9412 all-purpose grain drill is not only extremely versatile, but one of the only mounted, true no-till grain drills on the market. In just a matter of minutes, it can be hand adjusted from conventional seeding to minimum-till seeding right on through heavy-residue no-till applications. Plus, the drive wheels can be slid in or out on the hex shafts for different row spacing.

Available in four widths from 10' to 20', this heavy-weight, rigid seeder adapts to either Category II or III hitches for close coupling and a tight turning radius that translates into greater maneuverability. Yet, it can be easily converted to a pull-type machine for use with a smaller tractor or one without a three-point hitch by simply adding Sunflower's transport pull hitch.

Sunflower - The Ultimate Answer




- 1. LOW-PROFILE GRAIN BOXES** - The 16-gauge metal box features seed capacities of 2.4 bushel per foot. Wide lids facilitate loading and easy cleanout. 3.0 bu. per foot on 12.5' models.
- 2. EXTRA HEAVY FRAMES** - Heavy-duty 3/8" x 7" x 7" main frames are coupled to a 3/8" x 3" x 5" opener frame to create a sound foundation for all Sunflower grain drills.
- 3. DRIVE MECHANISM** - The seed meter drive features maintenance-free steel sprockets, #50 HD chain, a spring-loaded chain idler and a spring-loaded drive wheel to ensure constant soil contact.
- 4. OPTIONAL SEED METER DIVIDER TENTS** - Divider tents facilitate seed flow to meters and minimize the need for hand cleaning of hopper bottoms.
- 5. ACCURATE METERING BUT EASY ON THE SEEDS** - All Sunflower grain drills feature gentle nylon seed cups with six internal flutes, which accurately meter a wide variety of seeds without causing seed damage.
- 6. 8" OPENER STAGGER** - Allows crop residue to flow through the openers and not gather within. All Sunflower grain drills feature a full 8" of front-to-rear opener stagger that allows crop residue to flow through the openers without bunching or gathering.
- 7. QUICK MANUAL ADJUSTMENTS** - Simple, easy seed meter adjustments can be performed by turning a single star nut which sets all connected meters at the same time, to the same rate.
- 8. QUICK-ATTACH 3-POINT MOUNT** - Standard feature on all Sunflower Transport Pull Hitches, the quick-attach allows the operator to hook up or unhook from the grain drill quickly and with ease.
- 9. SINGLE POINT DEPTH CONTROL** - Allows the operator to set a positive drilling depth or can be set to transfer all weight of the 3-point hitch to the drill when conditions warrant.
- 10. OPTIONAL OPENER SHIELD ASSEMBLIES** - Align and deflect stalk residue to prevent buildup in the drill openers.

9412 GRAIN DRILL SPECS

MODEL NUMBER	9412-10	9412-12
Width (m)	10' (3)	12' 6" (3.8)
# Openers 7 1/2" (191 mm) Spacing	16	20
# Openers 10" (254 mm) Spacing	12	15
Hopper Capacity bu (L)	24 (774)	37.5 (321)
Weight (7 1/2" (191 mm) Spacing) (kg)	3,876 lbs. (1758)	5,110 lbs. (2318)
(10" (254 mm) Spacing) (kg)	3,326 lbs. (1509)	4,423 lbs. (2006)
Transport Width (m)	10' 6" (3.2)	13' 5" (4.1)
Transport Pull Hitch (kg)	1,650 lbs. (1748)	1,650 lbs. (748)

Note: Above specifications may vary slightly based on tires, hydraulic system, or other possible variances. We are continually striving to improve our machines; therefore, these specifications are subject to change without notice.



5



6



7



8



9



10