

WESTFIELD®

Westfield Industries Ltd.

A division of Ag Growth Industries

Box 39, Rosenort, Manitoba Canada R0G 1W0

Phone: (204) 746-2396 Fax: (204) 746-2679

Website: www.grainaugers.com

Litho'd in Canada UA02/02cgRpt

HORSE POWER REQUIREMENTS*

LENGTH	4"	6"	7"	8"	10"	13"
11'	3/4	●	●	●	●	●
16'-21'	3/4-1	1 1/2-2	2-3	3	3-5	10
26'-31'	1-1 1/2	3	3-5	5	5-7 1/2	15
36'-41'	1 1/2-2	3-5	5-7 1/2	5-7 1/2	7 1/2-10	20
46'-51'	2-3	5	7 1/2	7 1/2-10	10-15	●
56'-61'	●	7 1/2	7 1/2-10	10	15-20	●

*With dry grain. Full tube of high moisture grain will require additional horsepower.

SPECIFICATIONS

	4"	6"	7"	8"	10"	13"
Recommended pulley size for 1750RPM motors	1A 2" - 2 1/4"	2B 3 1/2" - 4"	2B 3 1/2" - 4"	2B 3 1/4" - 3 1/2"	2B 3 1/4" - 3 1/2"	3B 3 1/4" - 3 1/2"
Flight speed	440 - 490	480 - 550	480 - 550	445 - 480	380 - 410	355 - 380
Auger pulley supplied	1A 8"	2B 12.7"	2B 12.7"	2B 12.7"	2B 15"	3B 16"
Belt(s) supplied	1 - A33	2 - B48	2 - B51	2 - B51	2 - B62	3 - B67
Extensions available	5' - 10'	5' - 10' - 15'	5' - 10' - 15'	5' - 10' - 15'	5' - 10' - 15'	5' - 10' - 20'
Tube gauge	16	16	16	14	14	12
Flight gauge	13	12	12	10	7	7

NOTE: Recommended motor pulley sizes are for 1750 RPM electric motors. For intermittent feed, a slightly smaller pulley will allow easier startup under load.

Specifications are subject to change without notice or obligation.



SAFETY FIRST

Some features are shown with safety shields removed for clarity. DO NOT operate auger with safety shields removed. Read and understand operators manual before operating.

