

Front-End Loader - 95 Series

Model	95	195	295	395	495	495 S
Maximum lift height to pivot pin (in)	78	90	112	118	127	122
Reach at maximum lift height (in)	N/A	15	22	20	28	33
Maximum dump angle (deg)	45	40	25	27	38	38
Maximum rollback angle (deg)	14	19	32	31	23	20
Digging depth (in)	3.9	3.3	2.2	2.9	5.2	5.2
Overall height in carry position (in)	48	51	59	59	67	67
Lift capacity to maximum height - at pivot point (lb.) optional cylinder	525	1150	1625 2775	1500 2650	2075 3300	2100 3340
Lift capacity to maximum height (lb.) optional cylinder	350	775	1150 1975	1075 1875	1375 2175	1400 2214
Breakout force - at pivot point (lb.) optional cylinder	1200	2175	2775 4675	2425 4150	3475 5375	3750 5775
Breakout force (lb.) optional cylinder	850	1600	2150 3600	1900 3275	2500 3875	2650 4075
Hydraulic pressure rating/flow rate (psi)/(gpm)	1800/5	2000/5	2500/10		2500/10	
Tractor size (HP @ normal duty)	15-25	20-35	30-45	35-75	50-100	
Weight (with bkt & mtg kit) (lb.)	475	775	1285	1515	2070	

Model	595	595 S	695	795	795 S	895	895 S
Maximum lift height to pivot pin (in)	136	131	150	161	154	168	168
Reach at maximum lift height (in)	32	37	30	26	34	29	41
Maximum dump angle (deg)	41	41	59	32	32	40	40
Maximum rollback angle (deg)	18	18	34	21	22	22	22
Digging depth (in)	5.5	5.5	9.1	4.4	4.4	4.5	4.5
Overall height in carry position (in)	75	75	79	81	80	86	86
Lift capacity to maximum height - at pivot point (lb.) optional cylinder	2425 3775	2450 3800	3275	3100	3175	4675	4675
Lift capacity to maximum height (lb.) optional cylinder	1650 2575	1675 2614	2225	2075	2100	3325	3325
Breakout force - at pivot point (lb.) optional cylinder	5425 8200	5825 8800	7375	6825	7500	10150	10150
Breakout force (lb.) optional cylinder	3875 5875	4125 6175	5400	5050	5425	7600	7600
Hydraulic pressure rating/flow rate (psi)/(gpm)	2500/15		2500/15	2500/15		2500/20	
Tractor size (HP @ normal duty)	50-120		75-150	75-150		130-190	
Weight (with bkt & mtg kit) (lb.)	2190		2585	2760		3390	