

# NUTRI-PLACER 940 PULL-TYPE APPLICATOR SPECIFICATIONS



# CASE IH NUTRI-PLACER 940 PULL-TYPE APPLICATOR

## Features

- 7-section fold, 5-section flex frame for ground contouring
- High, under-frame clearance for residue flow
- Heavy-duty running gear
- 23% increase in width
- Matched capacity to largest tractors in the industry
- Compatible with commodity air systems
- Slim design for narrow transport; excellent roading
- Proven, ground-engaging components for NH<sub>3</sub> retention
- Hydraulic, single-point depth control
- Independent, pivoting coulters
- High-clearance shank with adjustable holding power
- 15- and 30-inch (38 cm, 76 cm) row spacing
- All new rear hitch for simple, reliable hook-up
- Easy leveling turnbuckles for fore/aft pitch and wing wheel adjustment
- Reduced service requirements
- Heavy frame tube



PRODUCT SPECIFICATIONS

NUTRI-PLACER 940 PULL-TYPE APPLICATOR	50 FT. (15.2 M)	60 FT. (18.3 M)	65 FT. (19.8 M)
Frame Style	Pull-Type		
Standard Shank Configuration	20 Shank HCS on 30 in. (762 mm) Centers with Optional 24 in. (610 mm) Coulters	24 Shank HCS on 30 in. (762 mm) Centers with Optional 24 in. (610 mm) Coulters	26 Shank HCS on 30 in. (762 mm) Centers with Optional 24 in. (610 mm) Coulters
Optional Shank Configuration	N/A	47 Shank HCS on 15 in. (381 mm) Centers with No Coulters	51 Shank HCS on 15 in. (381 mm) Centers with No Coulters
Transport Height	13 ft. 9 in. (4.2 m)		
Transport Width	18 ft. 9 in. (5.7 m)		
Main Transport Wheels	Walking Tandem 4x16.5-16.1 14 ply (Optional Stubble-Resistant FI Tires with 8-Bolt Hubs)		
Wing Wheels	Walking Tandem 8x12.5L-15 10 ply (Optional Stubble-Resistant FI Tires with 6-Bolt Hubs)		
Outer Gauge Wheel	None		Pin Adjust 2x20.5-8 Load Range D
Weight	21,150 lb. (9752 kg)	22,500 lb. (10 206 kg)	23,000 lb. (10 433 kg)
Configuration	5-Section Flex, 5-Section Fold	5-Section Flex, 7-Section Fold (Fold Forward Outer Wing)	
HP Requirement	300-460 Engine HP	360-550 Engine HP	390-598 Engine HP
Knife Options	All Side Mounted		
Operating Speed	5-8 mph (8 - 12.9 kph)		
Depth Adjustment	Single-Point Hydraulic		
Hinge Lubrication	Composite Self-Lubricating Bushing		
Options	Constant Level Rear Hitch, 24 in. (61 cm) Coulters, 18 in. (46 cm) Dull or Notched Sealing Discs, Rear Cooler Mounting Bracket Kit		

SAFETY NEVER HURTS!™ Always read the Operator's Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided. CNH America LLC reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice. Availability of some models and equipment builds varies according to the country in which the equipment is used.

©2012 CNH America LLC. All rights reserved. Case IH is a registered trademark of CNH America LLC. Any trademarks referred to herein, in association with goods and/or services of companies other than CNH America LLC, are the property of those respective companies. Printed in U.S.A. www.caseih.com CIH02071201 Replaces CIH5271001