



PMM/EX

Mulcher with swinging hammers rotor for excavators having a weight between 6 and 13 t.

Standard equipment: variable displacement hydraulic piston motor from 32 to 65 cc with double relief valve and anticavitation and brake function, protection hood, and adjustable skids.

Options: custom made attachment plate with pins, attachment plate with self levelling device, stronger bearing for the back roller, rotor equipped with heavy duty hammers or with "Y" flails.



PMM/EX

| Model | Power HP Min - Max | Requirements | | Excavators weight t. Min - Max | Working width inches | Weight lbs | Grinding diameter inches (max) | Teeth q.ty | |
|------------|-----------------------|---------------------------|---------------------------|--------------------------------------|----------------------------|---------------|--------------------------------------|----------------|-------------|
| | | Flow gal/min Min - Max | Pressure PSI Min - Max | | | | | hammers PMM | flails Y |
| PMM/EX 100 | 50 - 100 | 16 - 35 | 2600 - 3600 | 5 - 13 | 42 | 1147 | 3 | 12 | 12 |
| PMM/EX 125 | 50 - 100 | 16 - 35 | 2600 - 3600 | 6 - 13 | 51 | 1323 | 3 | 16 | 16 |
| PMM/EX 150 | 50 - 100 | 16 - 35 | 2600 - 3600 | 6 - 13 | 61 | 1499 | 3 | 18 | 18 |
| PMM/EX 175 | 50 - 100 | 16 - 35 | 2600 - 3600 | 7 - 13 | 70 | 1676 | 3 | 22 | 22 |

Data refers to the machine without options.



Hammer type PMM



Flail type "Y"