

ARBUS VALÊNCIA




Wide swath spraying
indispensable for big
trees groves.

ON THE LEVEL OF YOUR
SPRAYING NEEDS.



TOTAL COVERAGE

The volute assembled higher than the conventional providing a perfect coverage from bottom to top trees.



FAN. Mounted on a position above the conventional. It has nylon blades, resists chemicals action and requires low start torque. Its great air volume makes the chemicals penetrate the tree easily.



NOZZLES. Made of ceramic resistant to abrasion. Adjustable nozzle bodies, equipped with individual shut off valves, permit to direct the spray mixture according to the size of trees.



WIDE ANGLE CV JOINT SHAFT. Permits to make turns of up to 75° without disengaging the PTO.



MASTERFLOW CONTROL VALVE. Maintains the same volume of application when the tractor's speed changes in a same gear along the spray path or at the end of rows.

TECHNICAL SPECIFICATIONS

Tank 2,000 liters (530 gal); fiberglass
Dimensions length: 4.00 m (13' 1 1/2")
width: 1.75 m (5' 8 7/8")
height: 2.60 m (8' 6 3/8")

Weight 885 kg (1,950 lbs)
Pump model: JP-150
pumping capacity: 150 l/min (40 gpm)
at 540 rpm [Optional: 190 l/min (50 gpm)]
working pressure: 28 kg/cm² (400 psi)

Nozzles model J5-2 (number: 25)
Fan nylon blades; 2,050 rpm
air volume: 19.5 m³/s (688 cu.ft./s)
air speed: 112 km/h (69 mph)



Jacto Customers Are Happy Customers.

MÁQUINAS AGRÍCOLAS JACTO S. A.

Rua Dr. Luiz Miranda, 1650

17580-000 - Pompéia - SP - Brasil

Tel.: 55 14 3405 2100 - Fax: 55 14 4521916

jacto@jacto.com.br

Jacto reserves the right to change its products without prior notice.