

## Propeller Series Snowblower

MODEL	PR500	PR600	PR660	PR740	PR840	PR840G	PR960	PR1080	PR1200
Cutting width	50"	60"	66"	74"	84"	84"	96"	108"	120"
Cutting height	24"	24"	24"	25"	25"	25"	36"	41"	41"
Replaceable cutting edge	N/A	N/A	N/A	N/A	N/A	N/A	Optional	Yes	Yes
Fan	4-blade	4-blade	4-blade	4-blade	4-blade	4-blade	4-blade	4-blade	4-blade
Fan diameter	22"	22"	22"	23"	23"	23"	32"	34"	34"
Replaceable fan housing	N/A	N/A	N/A	N/A	N/A	N/A	N/A	7 gauge	7 gauge
Drive fan	540 RPM open gear	540 RPM open gear	540 RPM open gear	540 RPM open gear	540 RPM open gear	540 RPM oil bath gearbox	540 RPM oil bath gearbox	1000 RPM oil bath	1000 RPM oil bath
Auger diameter	15"	15"	15"	15"	15"	15"	15" (dual)	15" (dual)	15" (dual)
No. of auger paddles	10	12	14	16	18	18	20, ea.	22, ea.	24, ea.
Auger drive	#50 chain	#50 chain	#50 chain	#50 chain	#50 chain	#50 chain	#60 chain	#80 chain	#80 chain
Spout rotator - manual (hand crank) - hydraulic	Standard	Standard	Standard	Optional	Optional	Optional	Optional	N/A	N/A
	Optional	Optional	Optional	Standard	Standard	Standard	Standard	Standard	Standard
Spout deflector - manual (6 position) - hydraulic	Standard	Standard	Standard	Standard	Standard	Standard	Standard	N/A	N/A
	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Standard	Standard
Skid shoes	Adjustable and replaceable	Adjustable and replaceable	Adjustable and replaceable	Adjustable and replaceable	Adjustable and replaceable	Adjustable and replaceable	Adjustable and replaceable	Adjustable and replaceable	Adjustable and replaceable
Hitch category	Cat. I std Cat. I Q.H. std	Cat. I std Cat. I Q.H. std	Cat. I std Cat. I Q.H. std	Cat. I std Cat. II bushings	Cat. I & II std Cat. II Q.H. std Cat. III Q.H. narrow	Cat. I & II std Cat. II Q.H. std Cat. III Q.H. narrow	Cat. II std Cat. II Q.H. std Cat. III Q.H. narrow	Cat. II std Cat. III Q.H. std Cat. III Q.H. narrow	Cat. II std Cat. III Q.H. std Cat. III Q.H. narrow
Hitch adjustment	4 position	4 position	4 position	2 position	2 position	2 position	Fixed	2 position	2 position
Tractor requirement	15 - 30 hp	20 - 40 hp	22 - 40 hp	40 - 70 hp	60 - 90 hp	60 - 90 hp	90 - 125 hp	120 - 180 hp	180-225 hp
Weight	422 lb	470 lb	515 lb	756 lb	848 lb	878 lb	1243 lb	2398 lb	2600 lbs