

# 1212 DISC HARROW

*Sunflower strength in a small package.*

Smaller acreage needs shouldn't mean settling for a light-weight disc harrow. That's certainly not the case with the Sunflower Model 1212. Built with all the strength and performance features found on larger Sunflower disc harrows — including a heavy mainframe — the Model 1212 is capable of performing primary and finish discing operations in even the toughest conditions. Choose from four rigid-frame models that match tractors up to 110 horsepower and discover why Sunflower is called North America's best built disc.

**Sunflower - The Ultimate Answer**



- 1. TRANSPORT SAFETY** - Safety lighting and SMV sign are standard equipment on every Sunflower machine.
- 2. FAST, EASY LEVELING** - Leveling the disc from front-to-rear is very simple with the easily accessible leveling screw. Heavy-duty compression springs cushion the front and rear gangs when crossing ditches or rough terrain.
- 3. DUAL WHEELS** - Dual wheels provide stability and even penetration across the width of the machine. 2" slip in spindles with triple lip seals will provide years of trouble-free service. Dual wheels are standard on 13'-15' models and optional on the 10'-12' machines.
- 4. C-FLEX™ BEARING STANDARDS** - C-Flex™ bearing standards absorb disc gang shock created by stumps, rocks, and normal discing. This extends bearing, spool and disc blade life.
- 5. MAINTENANCE-FREE LIFT** - Lift system is equipped with maintenance-free UHMW sleeves which eliminates the high wear, metal-to-metal contact points.
- 6. SOLID COMPONENTS THROUGHOUT** - Available with 22" or 24" disc blades with 8 1/2" spacing, which enhance residue coverage and increase ability to penetrate the soil. Large 1 3/4" gang shafts with a spring washer on the ends of the gangs, provide a solid foundation for maximum gang performance.
- 7. SELF-ADJUSTING SCRAPERS** - C-Flex™ bearing arm mounted disc blade scrapers stay in adjustment moving with the disc gangs, unlike frame mounted scraper assemblies.
- 8. VERSATILE HITCH** - Double lip hitch clevis is standard.

## 1212 DISC HARROW SPECS

MODEL NUMBER	CUTTING WIDTH (m)	TRANSPORT WIDTH (m)	*EST. WT. (kg)	WEIGHT PER FT. OF CUT (kg)
1212-10	10'-6" (3.2)	11'-4" (3.5)	3,978 lbs. (1804)	398 lbs. (180)
1212-12	11'-10" (3.4)	12'-8" (4)	4,199 lbs. (1904)	350 lbs. (159)
1212-13	13'-3" (4)	14'-1" (4.3)	4,851 lbs. (2200)	373 lbs. (169)
1212-15	14'-7" (4.5)	15'-5" (4.7)	5,069 lbs. (2299)	337 lbs. (153)

\*Weight is figured with 22" blades.

We are continually striving to improve our machines; therefore, these specifications are subject to change without notice.

