

<b>DIMENSIONS</b>	<b>1105</b>	<b>1205</b>	<b>1305</b>	<b>1500</b>
<b>Width – overall</b>				
Flotation	14'	14'	14'	N/A
Row crop 30"	12' 7"	12' 7"	12' 7"	N/A
Row crop, wide row	15' 4"	15' 4"	15' 4"	N/A
Track	13'	13'	13'	13'
<b>Length – total</b>	<b>31' 7"</b>	<b>34' 11"</b>	<b>34' 11"</b>	<b>38' 10"</b>
<b>Height – overall</b>	<b>11' 4"</b>	<b>10' 10"</b>	<b>11' 4"</b>	<b>11' 4"</b>

**SPECIFICATIONS**

<b>Weight</b>				
Flotation (empty)	24,900 lbs.	25,190 lbs.	25,400 lbs.	N/A
Row crop (empty)	27,500 lbs.	28,260 lbs.	28,470 lbs.	N/A
Track (empty)	31,000 lbs.	31,470 lbs.	31,680 lbs.	35,180 lbs.
Hitch (empty)	3,950 lbs.	4,000 lbs.	4,040 lbs.	5,250 lbs.
Hitch (loaded) <sup>1</sup>	6,280 lbs.	6,540 lbs.	6,600 lbs.	7,380 lbs.
<b>Capacity</b>				
Heaped capacity - tires	1,250 bu.	1,350 bu.	1,450 bu.	N/A
Heaped capacity - tracks	1,300 bu.	1,400 bu.	1,500 bu.	1,700 bu.
<b>Augers</b>				
Vertical auger	24" Diameter	24" Diameter	24" Diameter	24" Diameter
Horizontal auger	22" Diameter	22" Diameter	22" Diameter	22" Diameter
<b>Flotation Tire</b>				
Hubs (cast ductile iron)	20 Bolt	20 Bolt	20 Bolt	N/A
Spindle	4 ½"	6"	6"	N/A
<b>Row Crop</b>				
Hubs (cast ductile iron)	4–10 Bolt	4–10 Bolt	4–10 Bolt	N/A
Spindle	4 ½"	4 ½"	4 ½"	N/A
<b>Track</b>				
Track width	36"	36"	36"	36"
Ground contact length	100"	100"	100"	108"
Total footprint (sq. in.)	7,214	7,214	7,214	7,776
End wheels (per track)	(2) 31 ½"	(2) 31 ½"	(2) 31 ½"	(2) 36 ½"
Mid wheels (per track)	4	4	4	4
<b>Other</b>				
Unload	750 bu/min	750 bu/min	750 bu/min	750 bu/min
PTO	1 ¾" - 1000 rpm	1 ¾" - 1000 rpm	1 ¾" - 1000 rpm	1 ¾" - 1000 rpm
Safety chains (grade 70)	(2) 40.5Klbs. Rated	(2) 40.5Klbs. Rated	(2) 40.5Klbs. Rated	(2) 40.5Klbs. Rated
Adjustable discharge spout	35°	35°	35°	35°
Drive belts	4-Band V Belts (2)	4-Band V Belts (2)	4-Band V Belts (2)	4-Band V Belts (2)
Hydraulic requirements	2 SCVs	2 SCVs	2 SCVs	2 SCVs

<sup>1</sup> Cart capacity and hitch weight are based on #2 corn at 15% moisture (56lb test weight). Cart capacity and hitch weight may vary based on crop type, grade, moisture and other environmental factors.

<sup>2</sup> Bushels per minute may vary with moisture content of grain and/or PTO rpm.