


# R260

# SKID LOADERS



**GEHL**®

Capacities		Metric	Imperial
Rated Operating Capacity		1179 kg	2599 lb
Rated Operating Capacity with Optional Counterweight		1261 kg	2780 lb
Unladen weight		3719 kg	8199 lb
Weight and dimensions			
Overall Operating Height - Fully Raised	h27	4089 mm	161 in
Height to Hinge Pin – Fully Raised	h28	3124 mm	123 in
Overall Height to Top of ROPS	h17	2057 mm	81 in
Dump angle at full height	a5	40 °	40 °
Dump height	h29	2388 mm	94 in
Overall length with bucket	l16	3632 mm	143 in
Dump reach - Full height		686 mm	27 in
Rollback at ground		28 °	28 °
Seat to ground height	h30	1016 mm	40 in
Wheelbase	y	1257 mm	49 in
Overall width less bucket	b1	1712 mm	67 in
Bucket Width	e1	1778 mm	70 in
Ground clearance	m4	203 mm	8 in
Overall length - Less Bucket	l2	2832 mm	111 in
Clearance Radius - Front with Bucket	b18	2286 mm	90 in
Clearance Circle - Front without Bucket	b19	1422 mm	56 in
Clearance Circle - Rear	wa1	1626 mm	64 in
Performances			
Travel Speed with Two-Speed Option - Maximum		19.20 km/h	12 mi/h
Travel speed (unladen)		12.90 km/h	8 mi/h
Wheels			
Standard tyres		12.00x16.5 HD	12.00x16.5 HD
Engine			
Engine brand		Yanmar	Yanmar
Engine model		4TNV98CT-NMSLV Stage V	4TNV98CT-NMSLV Stage V
Engine norm		Stage V	Stage V
Gross Power (kW)		53.70 kW	53.70 kW
Net Power (kW)		52.70 kW	52.70 kW
Max. torque / Engine rotation		294 Nm / 2500 rpm	294 Nm / 2500 rpm
Battery		12 V	12 V
Starter (kW)		3 kW	3 kW
Hydraulics			
Standard flow - Auxiliary hydraulics		90 l/min	90 l/min
High-Flow Auxiliary Hydraulics – Option		132.50 l/min	132.50 l/min
Tank capacities			
Fuel tank		81.40 l	22 US gal
Reservoir Capacity Hydraulics		30.30 l	8 US gal
Displacement		3.30 l	0.87 US gal
Noise and vibration			
Environmental noise (LWA)		101 dB	101 dB
Whole-Body Vibration (ISO 2631-1)		0.96 m/s <sup>2</sup>	0.96 m/s <sup>2</sup>
Vibration to whole hand/arm		< 1.50 m/s <sup>2</sup>	< 1.50 m/s <sup>2</sup>



# GEHL®

Siège Social  
P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095  
Tel: (262) 334-9461 - Fax: (262) 338-7517  
[www.gehl.com](http://www.gehl.com)



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend